



ZANITARY® Series Sanitary Metal Rupture Disks



Safety through knowledge and performance.

ZANITARY® Series

Metal Rupture Disks

About ZOOK

ZOOK is a global market leader with over 90 years of manufacturing expertise, developing high-performance sanitary pressure relief solutions for the pharmaceutical, life sciences, biotech and food & beverage industries. ZOOK is committed to developing pressure relief solutions for customers requiring rigorous sanitary and hygienic standards while maximizing customers' productivity and keeping their people safe.

Global Reach

ZOOK has global locations in the USA, United Kingdom, Canada and Malaysia, with two state-of-the-art manufacturing facilities supplying to over 90 channel partners worldwide.



ZOOK Unique Technology

The new patent pending technology incorporates completely new and unique design and manufacturing processes. Utilizing a materials' natural properties, this exclusive process delivers a superior fatigue resistant and high performance rupture disk. Without indentations or crevices meeting the demanding geometric 3A requirements, the new ZANITARY disk design ensures that the process side is inherently smooth providing a high purity service.

ZANITARY® Series Metal Rupture Disks

The ZANITARY® Series is an advanced sanitary disk designed for the biotechnology, pharmaceutical and food processing industries. The new design effortlessly fits between standard sanitary ferrules.

Sanitary Rupture Disk Features

- Ideal for high purity and corrosion resistant service that is required from the Life Science Industry.
- Designed for non-fragmentation
- Solid metal robust design provides greater protection for low pressure rated disks
- Operating ratios up to 95% of the marked burst pressure.
For pressures under 40 psig (2.76 barg) see table.
- Plus Testing available for a true engineering 95% operating ratio with $\pm 5\%$ performance tolerance
- Passivation finish to reduce the possibility of contamination
- Standard surface finish 4 - 20 Ra μin (0.1 - 0.5 Ra μm)
- Disks suitable for Clean In Place (CIP) and Steam In Place (SIP)
- Withstands full vacuum without the need of a separate vacuum support
- Suitable for liquid, gas, or two-phase applications
- Damage ratio of 1.0 or less*
- Expected cycle life of this new disk technology is 30,000 with full vacuum cycling and approximately 5,000,000 without full vacuum
- Disks available in 316L and Hastelloy
- Suitable for use with NovAseptic flange mountings
- Unique design is Patent Pending
- No dents or crevices to the process side of the disk
- Ferrule design compliant and certified to 3A sanitary standard
- Sizes from 1"(25mm) through 4"(100mm)
- Cleaned for O₂ service available
- 3-dimensional stainless steel tag permanently laser engraved with disk information in accordance to ASME and PED
- No paint or enamel used on tagging to ensure non-contamination of the sterile environment.
- Electropolishing available meeting ASME BPE SF4
- CRN registered for use in Canada
- Complies ASME BPE Standard
- ASME UD, CE (PED) and TÜV compliance available



ZANITARY® Series Metal Rupture Disks

Ferrule Standard and NovAseptic Flanges

The ZANITARY® can be installed into the Tri-Clover, BS, DIN, and ISO Standard ferrules along with the NA tank connectors as per the following:

- Tri-Clover
- ASME BPE
- BS4825-3 1991
- ISO 2852-1993 (Second Edition 1883-06-15)
- DIN 32676-2001-02

Temperature Testing

Every batch of ZANITARY® disks is tested in environmental chambers at the coincident temperature as specified by the end-user. The use of chart compensation factors are not utilized to ensure the disk meets the exact operating environment as specified by the client.

Stress Relieving

During the production process, stresses are introduced into the disk membrane material from mechanical operations. A heat stress relieving process is applied to each disk to ensure these localized high stress points are eliminated to protect the operating performance of the disk. After stress relieving is complete, all disks are then processed through an eco-friendly passivation operation.

Welded Cartridge

Looking for a welded custom solution? The welded cartridge combines the ZANITARY® product with ZOOK's in-house welding technology:

- Creates a cartridge style design which eliminates risk of disk damage
- Eliminates the need to separate piping system, a true "plug and play" unit
- Eliminates the effect of misaligned or improper line loading on rupture disk
- Creates hermetic seals between disk and ferrule components upstream and downstream of cartridge
- Eliminates the risk of installation damage

Torque-Rite Nut Features

- An audible “click” indicating correct torque setting
- Maintains the recommended constant 50 inch/pounds force
- Retrofits all sanitary clamps, 1” to 4”
- No torque wrench or special training required
- Torque-rite® sanitary clamp nut (eliminates the problems associated with over/under tightening)



Optional
Torque-Rite® Nut

Options


- ZAN-L* A process side PFA Teflon liner provides extra protection from corrosion or viscous process build-up (PEEK liner required for 3A compliance).
- ZAN-BI* Equipped with ZOOK's Integral Burst Indicator.
- ZAN95 Factory tested to 100% of the low end of the tolerance for optimized performance in demanding applications.
- ZANEP Electropolishing available in accordance to ASME BPE SF4

Note: *The maximum temperature rating of rupture disks supplied with liners and BI's is lower than the base disk material.

Sensors and Detectors

- BI Burst Indicator Available*
 - Remote Sensor RDI-S Available
 - Leak Detector Device Available
- * Maximum temperature for a BI is 400°F (204°C)

Shown with optional BI
Burst Indicator and
EPDM gaskets



ECO-Friendly Packaging


- Packaging utilizes FDA compliant coating
- Eco-Friendly Packaging does not contain any plastic
- Individually packed
- Nitrogen atmosphere bagging available

Gaskets

All gasket materials available are certified to FDA USP Class VI.

Gaskets available (other materials on request):

- Black Viton
- EPDM
- Black and White Buna
- White PTFE (Teflon)
- Red and Clear Silicone



Minimum and Maximum Pressure Ratings - psig (barg) @ 72°F (22°C)

Disk Size	Minimum Burst Pressure (psig/barg)				Maximum Burst Pressure (psig/barg)	MNFA in ² (mm ²)	Tri-Clover Ferrule Dimensions in (mm)	
	316L	Hastelloy C276	ZAN-L*	ZAN-BI			Ferrule OD	Tube ID
1"	35	65	+10**	+5**	300	0.43	1.98	0.87
25 mm	2.41	4.48	0.69	0.34	20.7	277	50.29	22.10
1-1/2"	15	25	30	+5 psig of base material	250	1.08	1.98	1.37
40 mm	1.03	1.72	2.07		17.24	697	50.29	34.80
2"	11	25	25		180	2.05	2.52	1.87
50 mm	0.76	1.72	1.72		12.41	1323	64	47.50
2-1/2"	11	25	25		145	3.25	3.05	2.37
64 mm	0.76	1.72	1.72		10	2097	77.47	60.20
3"	11	20	20		120	4.71	3.58	2.87
80 mm	0.76	1.38	1.38		8.27	3052	90.93	72.90
4"	11	20	20		80	8.49	4.68	3.83
100 mm	0.76	1.38	1.38		5.52	5619	118.87	97.28
Max. Temp.	Dependant on the gasket material used							

Notes:

* For PFA Liner, contact ZOOK for PEEK minimums

** Add pressure to minimum for metal

- For materials, sizes, burst ratings and temperatures not shown, contact ZOOK
- Contact ZOOK for higher temperatures
- 1" disk size is under evaluation by ASME and PED

Manufacturing Design Range & Total Performance Tolerance

	ASME					PED			Operating Ratio
	Burst Pressure (psig)		Manufacturing Design Range	Burst Tolerance	Operating Ratio	Burst Pressure (barg)		Total Tolerance	
	Minimum	Maximum				Minimum	Maximum		
Premium	11.0	<15	0%	±1.3 psig	100%	0.690	<1.034	±0.090 barg	95%
Standard	11.0	<15	0%	±1.3 psig	95%	0.690	<1.034	±0.090 barg	90%
Premium	15.0	<26	0%	±2.0 psig	100%	1.034	<1.793	±0.138 barg	95%
Standard	15.0	<26	0%	±2.0 psig	95%	1.034	<1.793	±0.138 barg	90%
Premium	26.0	<40	0%	±2.0 psig	95%	1.793	<2.758	±0.138 barg	95%
Standard	26.0	<40	0%	±2.0 psig	90%	1.793	<2.758	±0.138 barg	90%
Premium	40	Max	0%	±5 %	95%	2.758	Max	±5%	95%
Standard	40	Max	0%	±5 %	90%*	2.758	Max	±5%	90%*

* Below 40psi(g), operating ratios are from the minimum of burst/total tolerance

Notes:

- 0% manufacturing range might not be available in all materials
- Burst tolerances are the maximum expected variation from the disk's marked burst pressure

Gaskets (other materials on request)

Material	Min. Temperature	Max Temperature
Black Buna-N▲	-20°F (-29°C)	230°F (110°C)
White Buna-N	-20°F (-29°C)	230°F (110°C)
Black EPDM▲	-67°F (-55°C)	347°F (175°C)
Black Viton▲	-0.4°F (-18°C)	400°F (204°C)
Clear Silicone	-65°F (-54°C)	400°F (204°C)
Red Silicone	-65°F (-54°C)	400°F (204°C)
PTFE▲	-20°F (-29°C)	500°F (260°C)

▲ - Stocked material

ZANITARY® Series

Metal Rupture Disks



The ZANITARY® Series includes a ground-breaking rupture disk technology for rigorous sanitary and hygienic applications, utilizing the patent pending ZOOK Unique technology. The innovative manufacturing process and advanced design provides the best solution for high-performance pressure relief solutions.

Industries



Pharmaceutical



Life Sciences



Biotechnology



Food & Beverage

Applications

◦ Autoclaves	◦ Drying & Mixing Equipment	◦ Process Piping
◦ Bioreactors	◦ Fermenters	◦ Process & Transport Vessels
◦ CIP & SIP Skids	◦ Filters	◦ Safety Valve Protection
◦ Clean Steam Piping	◦ Heat Exchangers	◦ Storage Tanks



ZANITARY® Series

Accessories and Differentiators

Sanitary Clamps

ZOOK offers tri-clamp fittings for use with sensors and ZANITARY® Series disks. Options are also available for high burst pressure disks.



Torque Rite Nut

The Torque Rite Nut retrofits all sanitary clamps, with no torque wrench or special training required and eliminates the problems associated with over/under tightening. An audible “click” indicates the correct inch/pounds force maintaining the recommended constant 50 inch/pounds force.

RDI-S Sensor

The RDI-S is a one-time use sensor that installs into a sanitary spool located on the ventside of a sanitary bursting disk assembly. Upon rupture of the disk, the RDI-S alarm circuit is opened by the flowing media. Fits easily into existing piping systems.



Sanitary Ferrules

ZOOK can supply 316L ferrule connections and spool pieces to meet the appropriate standard required by the customer.





SERVING AMERICA, CENTRAL & SOUTH AMERICA

16809 Park Circle Drive
Chagrin Falls, Ohio 44022
United States

Toll Free: +1 800 543 1043
Phone: +1 440 543 1010
Fax: +1 440 543 4930
E-mail: sales@zookdisk.com
Website: www.zookdisk.com

SERVING EUROPE, MIDDLE EAST & AFRICA

Navigation House, Bridge Street
Killamarsh, Sheffield S21 1AL
United Kingdom

Phone: +44 (0) 1909 560999
Fax: +44 (0) 1909 560860
E-mail: sales.europe@zookdisk.com
Website: www.zookdisk.com

SERVING CANADA

4400 South Service Road
Burlington, Ontario L7L 5R8
Canada

Toll Free: +1 800 370 6057
Phone: +1 905 681 2885
Fax: +1 905 681 8838
E-mail: sales.canada@zookdisk.com
Website: www.zookdisk.com

SERVING ASIA PACIFIC

Unit No. 23A-05, Menara Landmark
No.12, Jalan Ngee Heng
80000 Johor Bahru, Johor
Malaysia

Phone: +60 (7) 2910099
Fax: +60 (7) 2910096
E-mail: sales.asia@zookdisk.com
Website: www.zookdisk.com

ALL OTHER INTERNATIONAL INQUIRIES

E-mail: sales@zookdisk.com

